

焼き入れリボン鋼＜SK材を焼入れしたもの＞

みがき焼き入れ鋼帯 寸法表 ※在庫・サイズ不定期変動あり(100幅以下はお問い合わせください)

注意事項

最小10m物・袋入り

青色表示は1000Lも有り

光輝アオ仕上

光輝白仕上

研磨白仕上

研磨青仕上

シート材

素材	SK4(SK95)		SK5(SK85)																SUP-10	SK5 (SK85)	SUP-10	
厚み	0.10	0.15	0.20	0.25	0.30	0.35	0.40	0.45	0.50	0.60	0.70	0.80	0.90	1.00	1.20	1.40	1.50	1.60	2.00	2.00	2.50	3.00
幅	10	12.7	3	6	3	6	3	12.7	4	5	3	5	8	3	10	12.7	30	10	15	250*1000	50*1000	50*1000
	12.7	25	5	7	5	12.7	4	25	5	6	5	8	12.7	5	12.7	16	100	12.7	20		50*2160	
	15	44	6	25	6	25	5	50	6	7	8	9.5	16	6	16	20		16	25			
	19	50	7	32	10	50	6	102	7	8	9.5	10	19	8	19	25		19	30			
	20	60	8	50	12.7	102	7		8	12.7	12.7	12.7	25	10	20	50		25	40			
	25	102	10	60	15		8		9.5	15	16	15	32	12.7	25	100		32	50			
	30	150	12.7	102	16		9.5		10	16	25	16	38	15	32			38	60			
	40		16	150	19		10		12.7	19	30	19	50	16	38			40	75			
	44		19		20		12.7		15	20	50	20	102	19	50			50	100			
	50		20		25		15		16	22	75	25		20	60			60				
	75		25		30		16		19	25	102	30		25	75			75				
	102		30		38		19		20	30		38		30	100			100				
	150		40		40		20		22	38		40		32				150				
			50		44		25		25	50		50		35								
			60		50		30		30	60		60		38								
			75		60		40		32	75		75		40								
			102		75		50		35	102		102		44								
			150		102		60		38	150		150		50								
					150		75		40					60								
							102		45					75								
							150		50					100								
									60					150								
									75					200								
									102													
									150													
									200													
硬さ	HV500±20								HV480±20					HV 445±20	HV435±20				HV470±30		HRC45±2	HRC42±2